



zero-one
systems inc.

Infrared Bullet Camera

CAM-BCIR667L



Features

- 1/3 inch Color CCD image sensor
- 1 Lux / F1.8, 0 Lux (10 meter IR on).
- 350 lines
- Indoor / Outdoor
- Day / Night
- Water Resistant
- IR LED: 12 units Infrared LED
- Effective Range: Over 10 Meters
- Automatic IR trigger-on under low illumination
- Automatic IR off under normal illumination

Includes

- Mounting Bracket
- 12VDC, 500mA UL AC Adapter
- Weather Canopy

Specifications

Imaging Element	1/3 inch Color CCD image sensor
Pixel Count	512(H)x492(V) <NTSC> / 512(H)x582(V) <PAL>
Resolution	350 TV lines ("Standard")
Min. Illumination	1 Lux / F1.8; 0 Lux (10 meter IR ON)
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60(1/50) to 1/100,000 sec.
Gamma Correction	0.45
White Balance	Auto white balance
AGC	Yes
Standard Board Lens	f 6.0mm / F1.8
Lens Angle	54°
Video Output	1.0 Vp-p composite, 75 Ω
Power Source	DC12V ± 10%
Current Consumption	110 mA (IR OFF), 260 mA (IR ON)
Water Resistance	IP 57
IR LED	12 units Infrared LED
Effective Range	Over 10 Meters
Dimension (mm)	64.6 (Φ) x 105 (L)
Gross Weight	0.58kg

Zero-One Systems Inc.

264 Gordon Avenue
Winnipeg MB R2L 0L8

www.zerooneinc.com
sales@zerooneinc.com

866.487.5586 TF
204.663.8742 PH
204.582.4059 FX